
5. (ONCE AMENDED) The multilayer-coated substrate of claim 1 or 2, wherein in the two or more layers, the coefficients of linear expansion of the respective layers change gradationally from the substrate toward the outermost layer.



7. (ONCE AMENDED) The multilayer-coated substrate of claim 1 or 2, wherein the substrate is a transparent body.

9. (ONCE AMENDED) The multilayer-coated substrate of claim 7, wherein the two or more layers satisfy the relationship

$$t_x/n_x = \lambda/4$$

wherein t_x is the thickness of an arbitrary layer, n_x is the refractive index thereof, and λ is the wavelength of the transmitted light.

- 11. (ONCE AMENDED) The multilayer-coated substrate of claim 9, wherein the transmitted light has a wavelength of from 380 to 2,000 nm.
- 12. (ONCE AMENDED) The multilayer-coated substrate of claims 1 or 2, wherein in the two or more layers, the outermost layer has been formed from methyltriethoxysilane and a lower layer has been formed from methyltriethoxysilane or tetraethoxysilane.

Please ADD the following new claims:

17. (ADDED) The multilayer-coated substrate of claim 8, wherein the two or more layers satisfy the relationship

$$t_x/n_x = \lambda/4$$

wherein t_x is the thickness of an arbitrary layer, n_x is the refractive index thereof, and λ is the wavelength of the transmitted light.

18. (ADDED) The multilayer-coated substrate of claim 10, wherein the transmitted light has a wavelength of from 380 to 2,000 nm.